



NOTE: When connector cavities are identified as "NO CONNECT" in the following table, there may be "Dummy (blunt cut) wires" or Cavities may be "Open", "Plugged, or "Flashed over" depending on vehicle option content.

Pin	Circuit	Wire Color	Gauge/Size	Function	Option
1	L144	BG/OG	0.75	RIGHT SIDE MARKER CONTROL	BASE
2	L60	WH/BG	0.75	RIGHT FRONT TURN LAMP DRIVER	
3	Z904	BK	0.75	GROUND	
4	L78	WH/OG	0.75	RIGHT FRONT PARK LAMP DRIVER	
5	L59	WH/DB	0.75	RIGHT DRL LAMP DRIVER	
6	Z904	BK	0.75	GROUND	



NOTE: When connector cavities are identified as "NO CONNECT" in the following table, there may be "Dummy (blunt cut) wires" or Cavities may be "Open", "Plugged, or "Flashed over" depending on vehicle option content.

Pin	Circuit	Wire Color	Gauge/Size	Function	Option
1	L552	BG/OG	0.35	RIGHT FRONT LIGHTING FAULT SENSE	PREMIUM
2	L60	WH/BG	0.75	RIGHT FRONT TURN LAMP DRIVER	
3	Z904	BK	0.75	GROUND	
4	L78	WH/OG	0.75	RIGHT FRONT PARK LAMP DRIVER	
5	L59	WH/DB	0.75	RIGHT DRL LAMP DRIVER	
6	Z904	BK	0.75	GROUND	