

ENGINE		Wrangler Sahara 4-door diesel 2.2 ATX 200 HP
No. of cylinders, layout		4 - in line
Displacement (cm ³)		2143
Bore x stroke (mm)		83.8 x 99.0
Valves per cylinder		4
Compression ratio		15,5:1
Max. power kW @ rpm		147 kW @ 3.500
Max. torque Nm @ rpm		450 Nm @ 2.000
Fuel injection		Diesel Direct Injection Common Rail
Fuel type		DIESEL
Fuel tank capacity (l)		81
UREA tank capacity (l)		18.9
GEARBOX		
Transmission		8-speed AUTOMATIC
1 st		4.714
2 nd		3.143
3 rd		2.106
4 th		1.667
5 th		1.285
6 th		1.000
7 th		0.839
8 th		0.667
Reverse		3.295
Final drive ratio		3.73
DRIVETRAIN		
Transfer case		Command-Trac Full Time 2.72:1
Crawl ratio		47.8

PERFORMANCE	
Acceleration: 0-100 km/h (s)	9,6
Top Speed (km/h)	180
CONSUMPTION AND EMISSIONS*	
Emission standard	EU6D
Fuel consumption – urban (l/100 km)	9,6
Fuel consumption – extra-urban (l/100 km)	6,5
Fuel consumption – combined (l/100 km)	7,6
CO ₂ emissions – urban (g/km)	254

CO ₂ emissions – extra-urban (g/km)	171
CO ₂ emissions – combined (g/km)	202

** The CO₂ and fuel consumption figures provided were measured using the measurement/correlation method for the NEDC cycle pursuant to Regulation (EU) 2017/1152-1153.*

The stated CO₂ and fuel consumption figures are not definitive and may evolve further to changes to the production cycle; more up-to-date values will be available at the chosen official FCA dealer.

WEIGHT AND DIMENSIONS	
Kerb weight STD. A (kg)	2.158
Weight distribution front/rear (%)	52/48
Max payload (kg)	507
Towing capacity (kg)	2495
Height (mm) (With standard hard top)	1838
Width (mm)	1.894
Lenght (mm)	4.882
Wheelbase (mm)	3008
Ground clearance (mm)	242
Load capacity (l) with seats in position	533
Load capacity (l) with flat rear seats	1.044

OTHER	
Approach/departure/breakover angle (degrees)	35.4/30.7/20
Turning Diameter (m)	12.28
Steering angle (inner/outer angle)	41°/34.4°
Steering Turns	3.24
Steering ratio	14.2
Water Fording [mm/kph]	760/8