

# WARN ZEON XD



**VR EVO**



**ZEON**



**ZEON XD**

<b>Available capacities</b>	8,000, 10,000, and 12,000 lb	8,000, 10,000, and 12,000 lb	10,000 and 12,000 lb
<b>No load line speed (amp draw)</b>	8,000: 24.8 ft/min (57A) 10,000: 27.1 ft/min (58A) 12,000: 26.2 ft/min (55A)	8,000: 35.0 ft/min (63A) 10,000: 33.0 ft/min (62A) 12,000: 28.1 ft/min (50A)	10,000: 39.7 ft/min (63A) 12,000: 31.1 ft/min (67A)
<b>Full load line speed (amp draw)</b>	8,000: 6.0 ft/min (298A) 10,000: 5.2 ft/min (358A) 12,000: 4.0 ft/min (396A)	8,000: 6.2 ft/min (413A) 10,000: 4.8 ft/min (409A) 12,000: 3.1 ft/min (438A)	10,000: 4.9 ft/min (458A) 12,000: 3.3 ft/min (466A)
<b>Wiring</b>	Traditional motor terminals, Albright contactor	Automotive grade bus bar, Albright contactor	Automotive grade bus bar, Albright contactor
<b>Ingress Protection</b>	Winch: IP68 rated	Winch: IP68 rated, paper gaskets Remote: IP68 rated	Winch: IP68 + IP69K rated, OEM grade O-rings Remote: IP68 rated
<b>Corrosion Protection</b>	240-hour salt spray, standard fasteners	408-hour salt spray, stainless fasteners	408-hour salt spray, OEM grade fasteners
<b>Controls</b>	Dual mode wired + wireless remote	Ruggedized wired remote	HUB wireless & ruggedized wired remote
<b>Winch Drum</b>	2.5" diameter steel drum,	3.2" diameter aluminum drum	3.2" diameter aluminum drum
<b>Rope Anchor</b>	Screw and thimble into drum flange	Patented thru-drum technology	Patented thru-drum technology
<b>Fairlead</b>	Black painted cast iron	Cast aluminum	Black anodized forged aluminum
<b>Dimensions</b>	21" L x 6.3" D x 10.1" H	24.3" x 7.2" x 10.6"	23.9" x 7.1" x 10.5"
<b>Final Assembly</b>	China	Oregon, USA	Oregon, USA
<b>Warranty</b>	Lifetime mechanical, 7 year electrical	Lifetime mechanical, 7 year electrical	Lifetime mechanical, 7 year electrical